



# INTELLISTRIPE 60

## General Information

<b>Interfaces</b>	<ul style="list-style-type: none"> <li>TTL</li> </ul>
<b>Dimensions</b>	<ul style="list-style-type: none"> <li>Height: 1.3 in (33 mm)</li> <li>Width: 2.6 in (66 mm)</li> <li>Length: 4.7 in (119,4 mm)</li> </ul>

## Specifications

<b>Voltage</b>	<ul style="list-style-type: none"> <li>Input with Latch: 5 VDC <math>\pm</math>5%</li> <li>No Latch: 2.7 VDC - 5.5 VDC</li> </ul>
<b>Current</b>	<ul style="list-style-type: none"> <li>2 mA per track</li> <li>300 mA for latch motor</li> </ul>
<b>Speed Range/Second</b>	<ul style="list-style-type: none"> <li>3 - 50 in (7,6 - 127 cm) per second</li> </ul>

## Environment

<b>Temperature</b>	<ul style="list-style-type: none"> <li>Operating: -13°F - 158°F (-25°C - 70°C)</li> <li>Storage: -40°F - 158°F (-40°C - 70°C)</li> </ul>
<b>Humidity</b>	<ul style="list-style-type: none"> <li>Operating: 10% - 90% non-condensing</li> <li>Storage: 10% - 90% non-condensing</li> </ul>
<b>Altitude</b>	<ul style="list-style-type: none"> <li>Operating: 0 - 10,000 ft (0 - 3,048 m)</li> <li>Storage: 0 - 50,000 ft (0 - 15,240 m)</li> </ul>

## Description

## P/N

<ul style="list-style-type: none"> <li>Tracks 1, 2, 3</li> <li>Front and side chassis</li> <li>Gate</li> <li>International bezel</li> <li>Metal bezel optional</li> </ul>	21160058
<ul style="list-style-type: none"> <li>Tracks 1, 2, 3</li> <li>Front and side chassis</li> <li>Gate</li> <li>Card latch with switch and PF</li> <li>No bezel</li> <li>Metal bezel optional</li> </ul>	21160098